


Swage nipples MSS SP 95 – BS 3799



Rozmery	3000 lbs			Hrúbka steny podľa ASME B36.10			Váha pre Sch80 (kg/ks)
	K		L				
	BS 3799	MSS SP95					
3/8" x 1/4"	76	64	16	Sch 40	Sch 80		0,50
1/2" x 3/8"	89	70	19	Sch 40	Sch 80		0,11
1/2" x 1/4"	89	70	19	Sch 40	Sch 80		0,11
3/4" x 1/2"	95	76	22	Sch 40	Sch 80	Sch 160	0,17
3/4" x 1/4"	95	76	22	Sch 40	Sch 80		0,17
1" x 3/4"	102	89	22	Sch 40	Sch 80	Sch 160	0,29
1" x 1/2"	102	89	22	Sch 40	Sch 80	Sch 160	0,29
1" x 1/4"	102	89	22	Sch 40	Sch 80	Sch 160	0,29
1 1/4" x 1"	114	102	25	Sch 40	Sch 80	Sch 160	0,45
1 1/2" x 1"	114	114	25	Sch 40	Sch 80	Sch 160	0,70
1 1/2" x 3/4"	114	114	25	Sch 40	Sch 80	Sch 160	0,70
1 1/2" x 1/2"	165	165	25	Sch 40	Sch 80	Sch 160	0,70
2" x 1 1/2"	165	165	29	Sch 40	Sch 80	Sch 160	1,45
2" x 1"	165	165	30	Sch 40	Sch 80	Sch 160	1,45
2 1/2" x 2"	178	178	32	Sch 40	Sch 80	Sch 160	2,00
3" x 2"	203	203	41	Sch 40	Sch 80	Sch 160	3,50
4" x 3"	229	229	48	Sch 40	Sch 80	Sch 160	4,80
4" x 2"	229	229	48	Sch 40	Sch 80	Sch 160	4,80

N+F Slovakia, s.r.o.
Vlčie hrdlo 1
SK – 824 12 Bratislava

+421 2 4055 2570-1
slovakia@nuf.eu

IČO: 45 254 273
IČ DPH: SK2022913849

N+F BOHEMIA, s.r.o.
Mírové náměstí 519/3d
CZ – 703 00 Ostrava Vítkovice

+420 724 256 715
+420 602 769 184
bohemia@nuf.eu

IČ: 47984660
DIČ: CZ47984660

Ukončenie
Plain ends (PE)
Bevelled ends (BE)
Threaded ends (TE)
NPT

Prevedenie
koncentrické
excentrické