




Sockolet redukovaný

Sockolet neredukovaný

Sockolet ASME B16.11



Pre potrubie STD a XS 3000 lbs

Rozmery	Redukované			Neredukované	
	A	B	Váha (kg/ks)	C	Váha (kg/ks)
1/8"	19	16	0,06		
1/4"	19	16	0,06		
3/8"	20,5	19	0,09		
1/2"	25,5	24	0,11	14,0	0,12
3/4"	27	30	0,17	19,0	0,19
1"	33,5	36,5	0,29	24,0	0,31
1 1/4"	33,5	44,5	0,41	32,0	0,45
1 1/2"	35	51	0,46	38,0	0,50
2"	38	65	0,80	49,0	0,87
2 1/2"	46	76	1,40	59,0	1,50
3"	51	93,5	2,00	73,5	2,15
3 1/2"	54	101,5	2,60	85,0	2,80
4"	57	120,5	3,30	97,0	3,50

Pre potrubie Sch 160 6000 lbs

Rozmery	Redukované		
	A	B	Váha (kg/ks)
1/4"	28,5	14	0,20
3/8"	28,5	14	0,20
1/2"	31,5	19	0,30
3/4"	36,5	26	0,50
1"	39,5	34	0,90
1 1/4"	39,5	38,0	0,85
1 1/2"	43	49,0	1,45
2"	52,5	59	2,75

Pre potrubie XXS 9000 lbs

Rozmery	Redukované		
	A	B	Váha (kg/ks)
1/2"	31,5	19	0,32
3/4"	36,5	26	0,55
1"	39,5	34	0,95
1 1/2"	43	49	1,50
2"	52,5	59,0	2,90

Uvedené rozmery (v mm) a hmotnosti (kg/ks) slúžia len na informatívne účely.