



Ohyby 3DN PN40

DN	D	R	l1	l3	t	90° (ON 132620.0)				45° (ON 132620.3)				30° (ON 132620.2)				15° (ON 132620.1)			
						a	l2	L*	Váha (kg/ks)	a	l2	L*	Váha (kg/ks)	a	l2	L*	Váha (kg/ks)	a	l2	L*	Váha (kg/ks)
10	14,0	30	100		1,5	130	47	247	0,11	112	24	224	0,10	108	16	216	0,10	104	8	208	0,10
15	21,3	45	100		2,6	145	71	271	0,33	119	35	235	0,28	112	24	224	0,27	106	12	212	0,25
20	26,9	60	100		2,6	160	94	294	0,46	125	47	247	0,39	116	31	231	0,36	108	16	216	0,34
25	33,7	75	100		2,6	175	118	318	0,63	131	59	259	0,52	120	39	239	0,48	110	20	220	0,44
32	42,4	96	150		2,6	246	151	451	1,15	190	75	375	0,96	176	50	350	0,89	163	25	325	0,83
40	48,3	120	150		2,6	270	188	488	1,43	200	94	394	1,15	182	63	363	1,06	166	31	331	0,97
50	60,3	150	150		2,9	300	236	536	2,20	212	118	418	1,72	190	79	379	1,56	170	39	339	1,39
65	76,1	195	250		3,2	445	306	806	4,63	331	153	653	3,75	302	102	602	3,46	275	51	551	3,17
80	88,9	240	250		3,6	490	377	877	6,64	349	188	688	5,21	314	126	626	4,74	282	63	563	4,26
100	114,3	300	400	800	4,0	700	471	1671	18,2	524	236	1436	15,7	480	157	1357	14,8	440	79	1279	13,9
125	139,7	375	400	800	4,5	775	589	1789	26,8	555	295	1495	22,4	501	196	1396	20,9	449	98	1298	19,5
150	168,3	450	400	800	5,0	850	707	1907	38,3	586	353	1553	31,2	521	236	1436	28,9	459	118	1318	26,5
200	219,1	600	600	1000	6,3	1200	942	2542	84,1	848	471	2071	68,6	761	314	1914	63,4	679	157	1757	58,2
250	273,0	750	600	1000	7,0	1350	1178	2778	128	911	589	2189	101	801	393	1993	91,5	699	196	1796	82,4
300	323,9	900	600	1000	8,0	1500	1414	3014	188	973	707	2307	144	841	471	2071	129	719	236	1836	114
350	355,6	1050	600	1000	9,0	1650	1649	3449	265	1035	825	2425	186	881	550	2150	165	738	275	1875	144
400	406,4	1200	800	2100	11,0	2000	1885	4785	522	1297	942	3842	411	1122	628	3528	377	957	314	3214	344
500	508,0	1500	800	2100	14,0	2300	2356	5256	899	1421	1178	4078	697	1202	785	3685	630	997	393	3293	563

* L) napriamená dĺžka oblúka

Ohyby dodávame podľa
EN 13480, EN 12952, ON 132620