


Oblúky NPT F – F, 90° ASME B16.11

Rozmery	3000 lbs				6000 lbs			
	A	H	G	Váha (kg/ks)	A	H	G	Váha (kg/ks)
1/4"	25	25	3,30	0,16	28	33	6,60	0,30
3/8"	28	33	3,51	0,32	33	38	6,98	0,48
1/2"	33	38	4,09	0,44	38	46	8,15	0,75
3/4"	38	46	4,32	0,68	44	56	8,53	1,21
1"	44	56	4,98	1,05	51	62	9,93	1,62
1 1/4"	51	62	5,28	1,26	60	75	10,59	2,73
1 1/2"	60	75	5,50	2,43	64	84	11,07	3,57
2"	64	84	7,14	3,35	83	102	12,09	6,16
2 1/2"	83	102	7,65	5,38	95	121	15,29	9,36
3"	95	121	8,84	8,53	106	146	16,64	17,10
4"	114	152	11,18	17,00	114	152	18,67	



Oblúky NPT F – F, 45° ASME B16.11

Rozmery	3000 lbs				6000 lbs			
	C	H	G	Váha (kg/ks)	C	H	G	Váha (kg/ks)
1/4"	19	25	3,30	0,14	22	33	6,60	0,27
3/8"	22	33	3,51	0,28	25	38	6,98	0,39
1/2"	25	38	4,09	0,36	28	46	8,15	0,66
3/4"	28	46	4,32	0,54	33	56	8,53	1,02
1"	33	56	4,98	0,90	35	62	9,93	1,35
1 1/4"	35	62	5,28	1,16	43	75	10,59	2,26
1 1/2"	43	75	5,50	1,86	44	84	11,07	3,08
2"	44	84	7,14	3,01	52	102	12,09	5,06
2 1/2"	52	102	7,65	4,73	64	121	15,29	7,74
3"	64	121	8,84	7,35	79	146	16,64	14,35
4"	79	152	11,18	15,00	79	152	18,67	

Uvedené rozmery (v mm) a hmotnosti (kg/ks) slúžia len na informatívne účely.